CLAIMS

What is claimed is:

1

2

1

2

3

1. A universal presentation device comprising
an electronic control device communicatively coupled with a computer system to
provide a control mechanism for the computer system; and
a coherent light source configured to provide a coherent light beam for pointing the
coherent light beam on an object,
wherein the electronic control device and the coherent light source are dimensioned to
form a substantially unitary device when at least one of the electronic control device
or the aphorent light course is energical

- 2. The universal presentation device in claim 1, wherein the substantially unitary device is dimensioned as a substantially elongated housing.
- 1 3. The universal presentation device in claim 2, wherein the coherent light beam 2 is dispensed from a substantially first side of the substantially elongated housing.
 - 4. The universal presentation device in claim 2, wherein a control mechanism of the electronic control device is mounted on substantially a first side of the substantially elongated housing.
- 1 5. The universal presentation device in claim 1, wherein a control mechanism of 2 the electronic control device is mounted on a surface of a housing.

1 6. The universal presentation device in claim 5, wherein a control mechanism of 2 the electronic control device and a lens of the coherent light source is mounted on 3 substantially a first end of the housing.

SUBARIT

. 2

3

1

2

3

1

2

3

1

2

3

4

5

- 7. The universal presentation device in claim 5, wherein a control mechanism of the electronic control device and a lens of the coherent light source mounted on substantially opposite ends of the housing.
- 1 8. The universal presentation device in claim 6, further comprising a writing
 2 mechanism, the writing mechanism mounted in a substantially same side of the housing as at
 3 least one of either the control mechanism or the lens.
 - 9. The universal presentation device in claim 3, wherein a control mechanism of the electronic control device is mounted on the substantially second side of the substantially elongated housing.
 - 10. The universal presentation device in claim 3, wherein a control mechanism of the electronic control device is mounted on the substantially first side of the substantially elongated housing.
 - 11. The universal presentation device in claim 1, further comprising a writing mechanism, wherein the writing mechanism couples with the electronic control device and the coherent light source to form a substantially unitary device when at least one from the group comprising the electronic control device, the coherent light source, and the writing mechanism is operational.

Case 4396 - 43 - 19414/04396/DOCS/987677.1

The universal presentation device in claim 1, wherein the electronic control

1

2

pointing device element.

12.

Case 4396 - 44 - 19414/04396/DOCS/987677.1

presentation element includes one from the group comprising a laser pointer element and a

- 1 18. The modular universal presentation device in claim 16, wherein the second 2 presentation element includes one from the group comprising a writing instrument element.
- 1 19. The modular universal-presentation device in claim 16, wherein the first presentation element and the second presentation element couple with a releasable locking assembly.